


NCAJS SMD CARRIER TAPE TRAY



SKU: 151470A



ADJUSTABLE TRAY FOR TAPED SMD COMPONENTS

NCAJ-S - Tray equipped with 5 adjustable guides for up to 4 pieces of SMD carrier tape of different widths.

It can be used for quick and easy PCB assembly with components from short pieces of tape.

Ideal also for reusing SMT devices, making SMD evaluations, supplying isolated components or just simply for short reminders of carrier tapes.

Easy and quick mounting with SMT machine.

Accessories (NOT included): Additional tape guides are available on request.

Specifications

- **Max. component height: 10 mm**
- Outer dimensions (WxDxH): 230 x 355 x 20 mm
- ESD safe: Yes
- Suitable for Cleanroom: Yes
- CEI 61340-5-1 compliant.

Set up

1. Set the tape guides (4 mm pitch)
2. Put the carrier tape into the tape guides
3. Secure the carrier tape using stopper pins
4. Set the carrier tape tray in your mounter.

Number and sizes of the tapes that can be placed

Tape width	Max. no. of tapes***
8 mm (0.35 Inch)	12
12 mm (0.47 Inch)	10
16 mm (0.63 Inch)	8
24 mm (0.94 Inch)	6
32 mm (1.26 Inch)	5
44 mm (1.73 Inch)	3
56 mm (2.21 Inch)	3
74 mm (2.91 Inch)	2

*** Please consider that only 5 tape guides are included in the standard delivery. **For the insertion of more than 4 tapes, additional tape guides are needed** (available on request).