


EM40 - ANTISTATIC ESD FLOOR PAINT (GREY, 5L)



SKU: 148148B



STATIC DISSIPATIVE FLOOR COATING

EM40 - ESD safe dissipative, water based acrylic paint in 5 litres cans.

Indicated for floorings subject to **low-stress conditions** with passage of **persons only**.
Suitable for both floorings and **walls**.

Laying method

- Ready to use, water based paint with low odour - Ready mixed (do not thin)
- Should be applied over a smooth, sealed floor, free from dirt, oil or any loose particles, **pre-treated with water based primer** (El.Mi product no.: 149369A)
- Rising damp lesser than 2% is strongly recommended for best results
- For the grounding, we recommend the installation of **one bonding point with copper strap** every 100 square meters
- Easy application by brush or roller
- Coverage (one coat): 10m² per Litre, 50m² per tin
- Two coats are recommended for best results
- Drying Time (20°C): Touch dry in 2 hours - Re-coat at 8-10 hours - Full cure in 3 days
- Equipment may be cleaned after use in warm water.

Specifications

- Colour (different colours are available on request): **RAL 7004 Grey - Satin finishing**
- Surface resistance: 10^5 - 10^8 Ohm/Square
- Resistance to ground: 10^5 - 10^8 Ohm
- **ESD properties:** IEC 61340-5-1/2 compliant
- Charge decay: MILB81705C compliant
- VOC Content: 60.5g/litre
- Typical Thickness: 40 micron per coat, two thin layers. Do not over apply thickness.