

KYZEN CYBERSOLV 141K LIQUID FLUX REMOVER (5KG)



SKU: 101492B



CYBERSOLV 141-X CLEANER BULK SIZE

Kyzen CYBERSOLV 141-X LIQUID - Non-flammable cleaning fluid made of organic solvents, developed for manual cleaning of PCBs and other applications requiring its unique solvency properties.

It is an excellent **dilution solvent for adhesives, greases and oils**.

May be used as a **cold cleaner for machined parts**.

Packaging: Steel container. Net content: **5 kg**.

[Click here for specifications](#)

Ideally suited for cleaning PTH and SMT electronic assemblies, connectors, cables and hybrid cables. It removes rosin, resin and synthetic polymeric flux residues from electronic circuitry. Effective on R, RMA, RA, Low-Solid and No-Clean fluxes. Not recommended for cleaning water based fluxes (ORH type). Compatible with most materials commonly used in electronic assembly manufacturing and cleaning processes.

Self-rinsing product: it dissolves the contaminant and then readily evaporates after cleaning.

Thanks to its very low surface tension, it can clean narrow traces and under some component gaps.

Specifications



CYBERSOLV 141-K is compliant with RoHS regulation.
 Its current formulation replaces CYBERSOLV 141-X and CYBERSOLV 141-R.

TYPICAL PROCESS (PCB CLEANING)

Process: Manual cleaning
Concentration: 100%
Temperature: Ambient
Surface tension: 23.5 dynes/cm
Rinsing: Not required
Drying (optional): Wipe

PRODUCT PROPERTIES

PH: N/A (solvent based)
Flash point: None to boiling
Boiling point: 95 °F / 35 °C
Liquid density: 9.4 lbs/gal
Water soluble: No
VOC, @ 100% 1097 g/l

PRODUCT IDENTIFIER IN THE SAFETY DATA SHEET:

Product name: **CYBERSOLV 141-K (AEROSOL)**

LABEL ELEMENTS:

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.



Warning. Pressurised container: May burst if heated. Harmful if swallowed. Harmful to aquatic life with long lasting effects.

Precautionary statements: Keep away from heat, hot surfaces, sparks, openflames and other ignition sources. No smoking - Do not pierce or burn, even after use - Avoid breathing dust/fume/gas/mist/vapours/spray - IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell - Rinse mouth - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F - Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional data: Contains 47.5% by mass of flammable components.

Contains: trans-dichloroethylene.

DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:

KYZEN - 430 Harding Industrial Drive, Nashville, TN 37211 - USA - www.KYZEN.com
 KYZEN BVBA - Zuidleiestraat 12 box 0A, 9880 Aalter - Belgium - Tel. +32 (0)50 395374.