

NOCLEAN TECHSPRAY DESOLDERING WICK (9 SIZES)



SKU: 1014



NO-CLEAN DESOLDERING WICK

Techspray No-Clean - Copper desoldering braid pre-coated with No-Clean flux. Available in 9 sizes. It does not leave behind residues of ionic flux that could collect and form branches called "dendrites". Different types of fluxes - if not cleaned properly - can cause dendrites that grow over time and eventually cause short circuits between traces or leads. Latent failures lead to costly returns and lower the quality perception of your products. Supplied with anti-static ESD safe plastic spool to prevent static build-up from damaging sensitive components. Meets or exceeds the following standards: MIL-F-14256, NASA NHB 5300, 4 (34-1), NASA NPC 200-4, NASA SP5002, IPC Standard-J-STD-004.

Available models

- 1820-5F White (#1) Dimensions: Width 0.9 mm, Length 1.5 m
- 1820-10F White (#1) Dimensions: Width 0.9 mm, Length 3.0 m
- 1822-5F Green (#3) Dimensions: Width 1.9 mm, Length 1.5 m
- 1822-10F Green (#3) Dimensions: Width 1.9 mm, Length 3.0 m
- 1822-100F Green (#3) Dimensions: Width 1.9 mm, Length 30.5 m
- 1823-5F Blue (#4) Dimensions: Width 2.5 mm, Length 1.5 m
- 1823-10F Blue (#4) Dimensions: Width 2.5 mm, Length 3.0 m

- 1823-100F Blue (#4) Dimensions: Width 2.5 mm, Length 30.5 m
- 1824-5F Brown (#5) Dimensions: Width 3.3 mm, Length 1.5 m.

VARIATIONS

SKU	Description	Dimensions
101449A		0.9 mm x 1.5 m
101408A		1.9 mm x 1.5 m
101408D		1.9 mm x 30.5 m
101408G		2.5 mm x 1.5 m
101408H		2.5 mm x 3.0 m
101408F		2.5 mm x 30.5 m
101408I		3.3 mm x 1.5 m
101408B		1.9 mm x 3.0 m
101449B		0.9 mm x 3.0 m