

## ADHESION PRIMER FOR SPRAY PAINT (400ML)



SKU: 640963B



### ADHESION PRIMER FOR SPRAY PAINT

#### One-component, solvent-containing primer in 400 ml spray can.

Professional product that allows the painting of plastic objects with spray varnish (El.Mi product no. 640963A).

Highly elastic, it guarantees **excellent adhesion**, quick application and fast drying.

Suitable for hard plastic furniture, exterior mirror housings, spoilers, bumpers, plastic parts on the floor.

In case of use with different substrates, it is recommended to **test the product** on a portion of the object to be coated, before proceeding with the definitive application.

Its glazed silver colour enables the control of the already painted surface.

#### Specifications

- Compatible substrates: ABS, PA, PC, POM, PP/EPDM, PPO, PUR, PVC, etc.
- **Yield: approx. 2.5 mq / 400 ml** (1 spray can) - Dry film thickness: max. 20 µm
- Colour: Transparent Silver
- Operating temperature: from +10 °C and up to 80% of relative humidity.

#### Method of use:

- Before proceeding with the treatment, the underground has to be clean, dry and **completely degreased**
- Shake the can vigorously before use, until you can hear the sound of the mixing balls
- Apply 2/3 coats in thin layers (the layer thickness should be approx. 3/5 µm) from a distance of approx. 20/30 cm
- After use, turn the can upside down and spray the nozzle empty (this operation prevents paint residues to get dried into the nozzle)
- DRYING TIMES:
  - Between each spray coat: **2/3 minutes**
  - Dust dry in **5/10 minutes**
  - Overpaintable after approx. **10 minutes**.

#### PRODUCT IDENTIFIER IN THE SAFETY DATA SHEET:

Product name: **Primer-Spray**

#### LABEL ELEMENTS:

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



*Danger. Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness.*

*Precautionary statements: If medical advice is needed, have product container or label at hand - Keep out of reach of children - Read label before use - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking - Do not spray on an open flame or other ignition source - Do not pierce or burn, even after use - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F - Dispose of contents/container in accordance with local/regional/national/international regulations.*

*Contains: Acetone, Ethyl acetate.*

#### DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:

*Contact us for information about the supplier of the safety data sheet.*