

## QUICKSTAT PLUS B1 - ESD FLOOR MAT ROLL (1.2X10M, TH. 3.5MM)



SKU: EL87669



### DARK GREY ESD FLOOR MAT (3.5MM)

**Quickstat Plus B1 - Anti-static ESD safe floor mat in 10 meters roll.**

Double-layer rubber mat (static-dissipative top layer / black conductive bottom layer).

"B1" **fire-resistant model**. Abrasion-resistant, suitable for **high loads**.

#### Specifications

- Material: Synthetic rubber
- Dimensions (WxL): **1.20 x 10 m** - Thickness: **3.5 mm**
- Upper layer colour: **Dark grey** - Finishing: Glossy
- ESD safe: Yes - Contact resistance (EN 1081):  $10^6 - 9 \times 10^7$  Ohm
- Slip-resistance: R10
- **Flame-retardant: B1**
- Other properties: Heat-insulating.



### Quickstat series ESD safe mats

Quickstat ESD safe floor mats are characterized by a very **easy, quick and cost-effective installation process**. Their conductivity depends on the highly conductive lower layer.

### INSTALLATION METHODS

- **In very small areas** (up to 2 sqm, using a single mat cut), Quickstat can be layed simply using a common double-sided adhesive tape, making possible an effective installation at extremely low costs. Earthing can be done by installing a grounding cable equipped with a 1 MOhm resistor.
- **In bigger areas** (and in any case, when using multiple mat cuts), the use of **conductive glue** is necessary, having previously installed a **copper grid** on the floor below, connected with earthing points.  
ATTENTION: Gluing is not recommended in environments with rising damp values higher than 2%.