

RFID TEST STATION WITH ACCESS LOG FOR ESD WRIST STRAPS



SKU: 159580A



EPA ACCESS CONTROL RFID TEST STATION

RFID TEST STATION - Tester for checking ESD wristbands, equipped with **RFID** identification system and **Ethernet** connection. Wall-mounted device to take measurements before entering an ESD protected area. Can be connected to an entrance barrier thanks to the integrated output relay.

Extendable to a complete system for checking wristbands and footwear by connecting a footplate (NOT included).

Available configurations: Kit with stand and footplate (El.Mi code 159580K), Kit with turnstile and footplate (El.Mi code 159580KIT).

List of accessories: RFID sensor for recording exits (El.Mi code 159580A), Footplate for column stand (El.Mi code 159580P), Column stand (cod. El.Mi 159580S), Footplate for turnstile (El.Mi code 159580D), Turnstile (El.Mi code 159580A), handrail for turnstile (El.Mi code 159580A).



Functioning

The system allows you to create up to **1000 unique users** and associate them with staff RFID badges. A radio frequency signal allows the tester's integrated contactless reader to recognize the operator's badge when shown. After performing the test, the operator displays the **access data** on the LCD screen (User, Date/Time, Measured values, PASS/FAIL result).

The internal **data logger** stores this data, making it available remotely via an Ethernet connection.

Specifications

- Power supply: 9-12 VDC, 1 A - Charger included (Banana plug, 5.5 / 2.1 mm)
- Wrist strap connections: **Press stud** (10 mm, 4 mm), **Banana** (4 mm)
- Measuring range: **50 kOhm - 2 GOhm** (Wrist strap), **50 kOhm - 2 GOhm** (Footwear)
- Measurement accuracy: $\pm 10\%$
- Test voltage (selectable): **50 V / 100 V**
- Max. no. of users: 1000
- Max. no. of accesses that the datalogger can store: 25000
- Fingerprint identification: No
- 125 KHz RFID card identification: Yes
- 13.56 MHz RFID card identification: Yes
- Identification time: < 1 sec.
- Graphic display LCD, 160 x 104 pixel
- Data interface: LAN RJ45
- Footplate and door-opener connector: 2 way Phoenix
- Relay output: max. 60 V, 1 A - 50 VA
- Overall dimensions: 225 x 168 x 38 mm
- Weight: 650 g.