


## WT2020M WELLER REWORK STATION (2-CHANNEL, 150W) | T0053445399



SKU: T0053445399



### WELLER WT 2020M MULTIFUNCTION STATION

WT2M unit 150W with tweezers 80W and soldering iron 40W

**WT 2020M - Weller digital rework station, 2 channels, 150 W 230 Vac.**

**Equipped with Micro tools sets** for Micro & Standard soldering and desoldering applications.

Thanks to intelligent power sharing, the WT 2M control unit **allows 2 users to work simultaneously**. The system features automatic tool recognition. If a connected tool has an integrated motion sensor, system allows automatic stand-by.

A clear menu structure allows for Intuitive use.

Weller product no.: **T0053445399**.

#### Scope of supply:

**WT 2M** (T0053443399) - Digital power unit with 2 channels, 150 W.

**WTMT SET** (T0051321499) – Kit includes:

- **WTMT** (T0051321199) - **Tweezers 80 W**, 12 V (tool without tips) for desoldering and soldering applications. Temperature range: **100-450 °C**. Heating time: **5 sec**. Tip family: RTWMS (Micro), RTWPS (Pico)
- **RTWMS 030 K** (T0050116099) - **Pair of tips** for WTMT tweezers, 80 W (**2 x 40 W**), 12 V. Suitable for use with Micro and Standard components, from 0504 up to 1608 (M to L)
- **WSR 211** (T0051518599) - **Safety rest** for WTMT desoldering tweezers, Stop-and-Go function, 2-in-1 cleaning system.

#### **WMRP SET** - Kit includes:

- **WMRP** (T0052917199N) - **Micro-soldering iron 40 W**, 12 V (tool without tip) with Active-Tip technology and stand-by function. Ideal for very small components with high energy demand. Temperature range: **100-450 °C**. Heating time: **3 sec**. Tip family: **RT**
- **RTM 013 S** (T0054460399N) - **RT Micro soldering tip, chisel (Ø 1.3 x 0.4 mm)**. High-performance active tip for Micro & Standard components
- **WSR 205** (T0051517999) - **Safety rest** for WMRP and WMRP MS soldering irons, 2-in-1 cleaning system.

#### **Specifications**

- Channels: 2
- Power: **150 W**
- Voltage: 230 / 23 V
- Temperature stability:  $\pm 2\text{ }^{\circ}\text{C}$
- Temperature accuracy:  $\pm 9\text{ }^{\circ}\text{C}$
- Overcurrent release: T40/B
- Fuse: T 0,8A
- ESD safe: Yes
- Stackable - Housing cover useable as storage
- Dimensions (WxDxH): 149 x 138 x 101 mm
- Weight: 3.10 kg
- UPC: **4003019441365**.