


WXD2 WELLER MULTIFUNCTION POWER UNIT (2-CHANNEL, 200W) | T0053426699N



SKU: T0053426399N



WXD DIGITAL CONTROL UNIT WITH 2 CHANNELS

Weller WXD 2 - Two-channel power unit for soldering and desoldering applications, 200 W (255W) / 230 V.

Requires **external compressed air supply** to operate (NOT included).

Weller product no.: **T0053426699N**.

Main features:

- Due to its power-range and **extremely short heating time**, the desoldering iron can easily handle jobs that would have been difficult in the past, including desoldering high mass PCBs
- Suction nozzle and solder cartridge can be changed quickly and easily
- Relatively low operating temperature (380 °C) and automatic standby mode controlled by the use sensor increase the service life of suction nozzles by a factor of 3
- A vacuum run-on time can be set to prevent the suction pump blocking.

Specifications

- Channels: 2

- Power: **200 W (255 W)**
- Supply voltage: 230 V, 50 Hz
- Adjustable temperature range (depends on tool): **50 - 550 °C** (150 - 999 °F)
- Temperature accuracy: $\pm 9\text{ °C}$ ($\pm 17\text{ °F}$)
- Temperature stability: $\pm 2\text{ °C}$ ($\pm 4\text{ °F}$)
- Vacuum max.: **55 kPa** (8 psi)
- Air consumption: **35 l/min**
- Compressed air connection: Outer diameter 6 mm (0.24 ") - Oil-free, dry compressed air
- Display: 255 x 128 pixels / Backlighting
- USB port: On / USB interface in front of firmware updates, parameterization and monitoring
- Equipotential bonding: Yes
- Fuse: T2 A
- WX compatible
- ESD-safe
- IPC-compliant
- Power cable: EMEA.