WT2023M WELLER REWORK STATION (2-CHANNEL, 150W) | T0053462699

SKU: T0053462699

WELLER WT2023M MULTIFUNCTION STATION

WT2M unit 150W with tweezers 80W and soldering iron 40(55)W

WT 2023M - **Weller digital rework station, 2 channels, 150 W** 230 Vac.
Equipped with Micro tools sets for Micro & Standard soldering and desoldering applications.
Thanks to intelligent power sharing, the WT 2M control unit **allows 2 users to work simultaneously**. The system features automatic tool recognition. If a connected tool has an integrated motion sensor, system allows automatic stand-by.
A clear menu structure allows for Intuitive use.
Weller product no.: **T0053462699**.

Scope of supply:

WT 2M (T0053443399) - Power unit with 2 channels, 150 W.

WTMT SET (T0051321499) - Kit includes:

elmi
Since 1969 The Partner for electronics industry

Fume extraction & Filtration
ESD Protection
Consumables
PCB Production
Counting and Weighing

Industrial furniture
Soldering & Desoldering
Mechanical Tools & Equipments
Optical inspection & Lighting
PCB & Electronics hardware

- **WTMT** (T0051321199) - **Tweezers 80 W**, 12 V (tool without tips) for desoldering and soldering applications. Temperature range: **100-450 °C**. Heating time: **5 sec**. Tip family: RTWMS (Micro), RTWPS (Pico)
- **RTWMS 030 K** (T0050116099) - **Pair of tips** for WTMT tweezers, 80 W (**2 x 40 W**), 12 V. Suitable for use with Micro & Standard components, from 0504 up to 1608 (M to L)
- **WSR 211** (T0051518599) - **Safety rest** for WTMT desoldering tweezers, Stop-and-Go function, 2-in-1 cleaning system.

<u>**WTMP MS SET**</u> (T0052924199) - Kit includes:

- **WTMP MS** (T0052923999) – **Micro soldering iron 40 W** (**55 W**) 12 Vac (tool without tip). Temperature range: **100-450 °C**. Heating time (50–350 °C): approx. **5 sec**. Stand-by function. Tip family: RTM MS (military standard)
- **RTM 013 S MS** (T0054461699N) – **RT Micro soldering tip, chisel** (**Ø 1.3 x 0.4 mm**). MIL-SPEC compliant, high-performance active tip for Micro & Standard components
- **WSR 205** (T0052924199) – **Safety rest** with double cleaning options.

Specifications

- Channels: 2
- Max. power of the control unit: **150 W**
- Voltage. 230 / 50 Hz
- Temperature range (depends on tool): **100 – 450/550 °C**
- Temperature stability: ± 2 °C
- Temperature accuracy: ± 9 °C
- Fuse: T 0,8
- ESD safe: Yes
- Stackable: Yes - Housing cover useable as storage
- Dimensions (WxDxH): 150 x 130 x 101 mm
- Weight: 1.9 kg
- UPC: **4003019449361**.