


1PK-3003F PINZA CRIMPATRICE ERGONOMICA (STRUTTURA)



Cod. 1PK3003F



PINZA PER CRIMPATURA PRO'SKIT

Crimpatrice con matrice intercambiabile (pinza senza utensile) a movimento ergonomico.

Forza meccanica superiore: aumenta la produttività, richiede il 40-50% in meno di forza per la crimpatura.

Codice Pro'sKit: **1PK-3003F**.

Caratteristiche

- Materiale: Acciaio S45C
- Lunghezza pinza: 260 mm.

Matrici intercambiabili disponibili su richiesta (NON incluse):

Complete set with die	Replacement die Set	Description & Applications	Following models are available
-----------------------	---------------------	----------------------------	--------------------------------

1PK-300F		Supercrimp crimp tool frame (Frame only without die)	
1PK-3003FD1	1PK-3003D1	22-10 AWG(0.325 mm ² -5.261mm ²).	☒ insulated terminals /color coded nests
1PK-3003FD2	1PK-3003D2	22-12 AWG(0.325 mm ² -3.31mm ²).	☒ Non insulated Open Barrel Connectors, Commercial Type
1PK-3003FD3	1PK-3003D3	Hex. 0.305,0.068, 0.228	☒ Cambridge CP-88, CP-89 BNC /TNC coax connectors with RG-58, RG-59/62 AU cables
1PK-3003FD4	1PK-3003D4	Round 0.195	☒ AMP Optimate Fiber-Optic SMA or SFR type connectors
1PK-3003FD5	1PK-3003D5	Hex 0.213, 0.178, 0.068,0.042	☒ RG-58, RG-174 and RG-8218 for both 50 and 75 ohm cables
1PK-3003FD6	1PK-3003D6	Hex, 0.429,0.100, 0.080	☒ N-Series and RG-8/11 Connectors
1PK-3003FD7	1PK-3003D7	Hex 0.178,0.128, 0.068	☒ RG-174, Mini 59 BNC/TNC Connectors
1PK-3003FD8	1PK-3003D8	Hex 0.324,0.178, 0.068	☒ RG-174, Belden-Type RG-8281 cables
1PK-3003FD9	1PK-3003D9	Hex 0.213,0.190, 0.068,0.042	☒ Plenum and Teflon Cables RG-58 and 59
1PK-3003FD10	1PK-3003D10	Hex 0.350,0.320, 0.255	☒ RG-59, RG-6, RG-8281, F-type CATV Connectors
1PK-3003FD11	1PK-3003D11	RJ-45, eight-position keyed or non-keyed modular plugs (excluding AMP)	☒

1PK-3003FD12	1PK-3003D12	RJ-11 two, four and six-position modular plugs	✗
1PK-3003FD13	1PK-3003D13	RJ-11 DEC MMJ six-position modular plugs with an offset release tab	✗
1PK-3003FD14	1PK-3003D14	AMP RJ-45 eight-position modular plugs/Primary strain relief crimp bar is located further back on die/modular plugs.	✗ RG-58, RG-59/62, BNC/TNC Coax connectors
1PK-3003FD15	1PK-3003D15	Hex, 0.255,0.213, 0.068	✗
1PK-3003FD16	1PK-3003D16	RJ-22 two and four-position handset modular plugs	✗
1PK-3003FD17	1PK-3003D17	Usable for RJ-45, 10 position modular plugs	✗
1PK-3003FD17-MA	1PK-3003D17-MA	Hirose RJ-48, 8 position modular plugs	✗
1PK-3003FD18	1PK-3003D18	22-10 AWG(0.325 mm ² -5.261mm ²)	✗ Usable for cord end terminals
1PK-3003FD19	1PK-3003D19	22-8 AWG 0.325 mm ² -8.367mm ²	✗ Usable for non insulated terminals 22-8 AWG
1PK-3003FD20	1PK-3003D20	Hex, 0.151 (3.84mm) 0.178(4.52mm) 0.213(5.41mm)	✗ Usable for Fiber-Optic SMA,SMB or SFR connectors
1PK-3003FD21	1PK-3003D21	16-26AWG(0.128 mm ² -1.31mm ²)	✗ Usable for miniature insulated rings & splices
1PK-3003FD22	1PK-3003D22	0.218(5.54mm) 0.049(1.24mm)	✗ Usable for AMP RG-58 dual crimp BNC/TNC coax connectors "O",